

SPECIFICATIONS

System capacity		
INPUT PV	Max.recommended PV panel power[W]	13kW
	Max.DC voltage[V]	1000V
	Input voltage range[V]	200-1000
	Norminal DC operating voltage[V]	620
	Max. input current(per mppt)[A]	12.5 / 12.5
	Max. short circuit current(per mppt)[A]	15.2 / 15.2
	MPPT voltage range[V]	250-850V
	No. of MPP trackers	2
	Strings per MPP tracker	1+1
BATTERY	Battery type	LiFePO4
	Norminal module energy[kwh]	2.56kWh
	Module voltage range[V]	86.4V~112V
	Norminal cabinet energy[kwh]	12.5kWh
	Cabinet voltage range[V]	432V~560V
	Norminal cabinet battery voltage [V]	512
	Max.charge/discharge current[A]	14/20
	Communication interfaces	RS485 / CAN
	Grid type	3Φ 400Vac
	Grid type	3Φ 400Vac
OUTPUT AC	Rated grid Frequency[Hz]	50/60
	Norminal AC outpout power[W]	10000
	Norminal AC output current[A]	15.2 / 14.4
	Max. AC output current[A]	16.5
	EPS rated voltage[V]	400
	EPS rated Frequency[Hz]	50Hz / 60Hz
	EPS rated power[VA]	10000
	EPS peak power[VA]	10000
EFFICIENCY	Max. PV to AC efficiency	98.2%
	Max. Battery to AC efficiency	97.5%
CERTIFICATION	PCS Certifications	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, CEI 0-21
	Battery safety certiifications	IEC62619,UN38.3
ENVIRONMENT LIMIT	IP Level	IP65(Inverter) IP55(Battery)
	PCS operating temperature range[°C]	-35~60 °C
	Battery operating temperature range[°C]	0-45
	Altitude[m]	4000
	Noise emission(typical)[dB]	<30
OTHERS	Cooling concept	Natural convection
	Insulating method	Transformerless
	Communication	External:APP/Web Battery:CAN2.0
	Warranty	5 years / 10 years(optional)
DIMENSIONS AND WEIGHT	Cabinet dimensions[mm]	660*1650*260mm
	Cabinet weight[kg]	195kg
	PCS dimensions[mm]	516x415x180mm
	PCS weight [kg]	25.1kg

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© Jinko Solar Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.